

Type	Rating	1/4"	3/8"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"
90° Elbows	3000	0.082	0.115	0.235	0.290	0.480	0.750	0.950	1.65	2.50	4.30	9.70
	6000	0.165	0.300	0.430	0.660	1.14	1.60	2.70	2.95	3.75	7.50	13.00
	9000			0.850	1.50	2.25	3.35	3.90	4.25			
45° Elbows	3000	0.078	0.100	0.192	0.250	0.380	0.580	0.830	1.15	2.05	3.40	9.00
	6000	0.120	0.240	0.300	0.530	0.860	1.07	1.90	2.35	3.00	6.00	10.30
	9000			0.600	1.18	1.55	2.40	3.45	3.55			
Tees	3000	0.118	0.190	0.310	0.400	0.580	0.910	1.25	2.10	3.15	5.25	13.50
	6000	0.210	0.400	0.555	0.910	1.41	1.75	3.56	4.10	6.25	10.30	17.00
	9000			1.04	1.85	2.32	3.50	4.55	5.00			
Crosses	3000	0.135	0.205	0.340	0.470	0.800	1.25	1.50	2.23	3.95	6.50	16.00
	6000	0.260	0.495	0.670	1.06	1.79	2.15	4.45	5.40	7.75	12.80	21.00
	9000			1.29	2.25	2.85	4.30	5.60	5.90			
Couplings	3000	0.050	0.065	0.105	0.152	0.260	0.370	0.420	0.770	1.10	1.40	2.35
	6000	0.070	0.095	0.148	0.335	0.370	0.490	0.680	1.24	1.81	2.80	3.50
	9000			0.230	0.410	0.640	0.800	0.890	1.63			
Half couplings	3000	0.058	0.085	0.180	0.205	0.320	0.410	0.560	0.960	1.50	2.00	3.40
	6000	0.075	0.110	0.205	0.300	0.470	0.600	1.05	1.60	2.30	2.65	5.00
	9000			0.260	0.410	0.650	0.800	1.25	2.10			
Caps	3000	0.035	0.060	0.135	0.175	0.295	0.510	0.650	0.920	1.40	2.50	3.50
	6000	0.075	0.135	0.180	0.210	0.460	0.700	0.885	1.20	2.00	3.25	5.50
	9000			0.235	0.280	0.600	0.880	1.10	1.60			
Unions	3000	0.180	0.225	0.385	0.520	0.730	1.20	1.56	2.30	5.00	7.15	15.25
	6000	0.350	0.550	1.15	1.57	2.10	2.65	3.60	5.50	9.50	19.00	25.00
	9000			1.25	1.70	2.35	2.95	4.75	6.50			
M/F Reducing Insert	3000	0.040	0.050	0.100	0.120	0.160	0.350	0.450	0.700			
	6000			0.250	0.300	0.350	0.500	0.650	1.00			
	9000			0.350	0.400	0.480	0.650	0.800	1.25			

#### Notes

Weights are in kgs

A) The weights are referred to straight pieces

B) The weight of reducing pieces: - Threaded tees, crosses, couplings and hexagonal nipples - Socket welding tees, crosses and couplings are to be increased of 15% every reducing unit

C) The weights of bushings are already considered for reducing unit.

D) Table "Run Pipes Ranges" shows for all types of outlets Megalet the correct run pipe (between min. and max. ND), thus simplifying the request taking into consideration the qualities covered by the same run pipe range.